

**LLDPE Widespec**

Gen. Variant: SDS\_US\_GHS

Version 1.0

Revision Date 04/21/2018

Print Date 08/23/2018

SDS No.: LLDBWS

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : LLDPE WIDESPEC  
CAS Number: 25087-34-7  
Chemical characterization : Polyethylene copolymer  
Chemical Name : 1-Butene, polymer with ethene  
Synonyms : Ethylene, polymer with 1-butene, Ethene-Butene copolymer

Identified uses : Manufacture of plastic articles by injection molding, extrusion or other conversion process.

Prohibited uses : FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications

Company : Trademark Plastics Corp  
494 Broad Street, Suite 200  
Newark NJ USA 07102

Telephone : Customer Service 908-925-5900  
Product Safety 908-925-5900

Emergency telephone : CHEMTREC USA 800-424-9300  
Trademark 908-925-5900

E-mail address info@trademarkplasticscorp.com

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

OSHA Hazard Category: Combustible Dust

**Label elements****Signal Word** : Warning**Hazard Statements** : May form combustible dust concentrations in air.**Other hazards**

No additional information available.

**3. Composition/information on ingredients****Mixtures**

# SAFETY DATA SHEET

**LLD Widespec**

Gen. Variant: SDS\_US\_GHS

Version 1.0

Revision Date 04/21/2018

Print Date 08/23/2018

SDS No.: LLDBWS

## Ingredients

Chemical Name	CAS-No.	Weight %
1-Butene, polymer with ethene	25087-34-7	> 99.5 %

Contains: Stabilizers

## SECTION 4. FIRST AID MEASURES

### First aid procedures

General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.

If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.  
In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air.  
Obtain medical attention.  
Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR)

In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer.  
Do not attempt to peel polymer from skin as this will remove the skin.  
Obtain immediate emergency medical attention if burn is deep or extensive.

In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists.

In case of eye contact with molten polymer:  
Continuously flush eye(s) with cool running water for at least 15 minutes.  
Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s).  
Immediately seek medical attention.

If swallowed : Adverse health effects due to ingestion are not anticipated.

### Notes to physician

Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.

Hazards : Dust contact with the eyes can lead to mechanical irritation.  
Molten polymer may cause thermal burns.

Treatment : Treatment of overexposure should be directed at the control of

# SAFETY DATA SHEET

**LLD Widespec**

Gen. Variant: SDS\_US\_GHS

Version 1.0

Revision Date 04/21/2018

Print Date 08/23/2018

SDS No.: LLDBWS

symptoms and the clinical condition of the patient.

## SECTION 5. FIRE-FIGHTING MEASURES

### Flammable properties

- Autoignition temperature : > 572 °F (300 °C)
- Lower explosion limit : The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution.
- Upper explosion limit : Not applicable.

### Fire fighting

- Suitable extinguishing media : SMALL FIRE:  
Use dry chemical, CO2, or water spray.
- LARGE FIRES:  
Use water spray hose nozzles from a safe location.
- Unsuitable extinguishing media : None known.
- Further information : Combustible particulate solid, will decompose under fire conditions.  
Calorific Value: 8000 - 11000 kcal/kg  
Fight fire from safe distance with hose lines or monitor nozzles.  
Heat from fire may melt, decompose polymer, and generate flammable vapors.  
Move containers from fire area if it can be done without risk.  
Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container.  
Always stay away from tanks engulfed in fire.  
Do not attempt to get on top of storage containers involved in fire.  
Cool storage containers with large volumes of water even after fire is out.

### Protective equipment and precautions for firefighters

- Specific hazards during fire fighting : Keep away from heat and sources of ignition.  
Dust particles from this product are combustible particulate solids that present a flash fire or explosion hazard when suspended in air.  
Polymer dust layer melts on the hot surface before ignition can occur  
In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).



# SAFETY DATA SHEET

**LLD Widespec**

Gen. Variant: SDS\_US\_GHS

Version 1.0

Revision Date 04/21/2018

Print Date 08/23/2018

SDS No.: LLDBWS

Special protective equipment for fire-fighters : Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Equip responders with proper protection.  
Creates dangerous slipping hazard on any hard smooth surface.  
Equip emergency responders with proper personal protective equipment (PPE)  
Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).  
Potential combustible dust hazard.  
Polymer particles create slipping hazard on hard smooth surfaces.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

Methods for containment /  
Methods for cleaning up : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk.  
On water, material is insoluble; collect and contain as any solid.  
All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.

## SECTION 7. HANDLING AND STORAGE

### Handling

Advice on safe handling : Avoid dust accumulation in enclosed space.  
Use dust collection systems designed per NFPA 654 to avoid dust accumulation.  
Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard.  
Polymer dust layer melts on the hot surface before ignition can occur  
Hot surface temperature shall be limited to less than 270°C to avoid direct ignition of a dust cloud.  
Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion  
Electrostatic charge may build during conveying or handling.  
Equipment handling polymer should be conductive and grounded (earthed) and bonded.  
Metal containers involved in the transfer of this material should be grounded and bonded.  
All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts.

# SAFETY DATA SHEET

**LLD Widespec**

Gen. Variant: SDS\_US\_GHS

Version 1.0

Revision Date 04/21/2018

Print Date 08/23/2018

SDS No.: LLDBWS

After handling, always wash hands thoroughly with soap and water.  
When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10.

Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

## Storage

Requirements for storage areas and containers

: Store in a dry location.

Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Degradation can occur because of exposure to temperature, light and oxidizing agent: trace amounts of light hydrocarbons, compounds of oxidation, aldehydes and acids can be generated.

Store away from excessive heat and away from strong oxidizing agents.

Keep container closed to prevent contamination.

Take measures to prevent the build up of electrostatic charge.

## 8. Exposure controls/personal protection

### Control parameters

#### Ingredients with workplace control parameters

#### Occupational Exposure Limits

Ingredients	CAS-No.	Type	Limit Value	Basis Revision Date	Additional Information
Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust		TWA	3 mg/m3 respirable	US (ACGIH) 2005	

# SAFETY DATA SHEET

**LLD Widespec**

Gen. Variant: SDS\_US\_GHS

Version 1.0

Revision Date 04/21/2018

Print Date 08/23/2018

SDS No.: LLD2017

Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust		TWA	15 mg/m3 total dust	US (OSHA) 2005	
Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust		TWA	5 mg/m3 respirable	US (OSHA) 2005	

Consult local authorities for acceptable exposure limits.

## Exposure controls

### Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used.

Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654

Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

### Personal protective equipment

- Respiratory protection : Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.  
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
Use appropriate respiratory protection where atmosphere exceeds recommended limits.  
Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
- Hand protection : Wear gloves that provide thermal protection where there is a potential for contact with heated material.
- Eye and face protection : Dust service goggles should be worn to prevent mechanical injury or other irritation to eyes due to airborne particles which may result from handling this product.
- Skin and body protection : Wear suitable protective clothing.
- Hygiene measures : Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be



# SAFETY DATA SHEET

**LLD Widespec**

Gen. Variant: SDS\_US\_GHS

Version 1.0

Revision Date 04/21/2018

Print Date 08/23/2018

SDS No.: LLD2017

performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.  
Use good personal hygiene practices.  
Wash hands before eating, drinking, smoking, or using toilet facilities.  
Take off contaminated clothing and wash before reuse.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### Appearance

Physical state : Powders or flakes.  
Color : Translucent to white  
Odor : Slight.

### Safety data

Lower explosion limit : The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution.  
Upper explosion limit : Not applicable.  
Flammability (solid, gas) : Polymer will burn but does not easily ignite.  
Oxidizing properties : Not considered an oxidizing agent.  
Autoignition temperature : > 572 °F (300 °C)  
Decomposition temperature : not determined  
pH : Not applicable.  
Melting point/range : 122 - 338 °F (50 - 170 °C)  
Boiling point/boiling range : Not applicable.  
Vapor pressure : Not applicable.  
Density : < 1 g/cm<sup>3</sup>  
Water solubility : Insoluble.  
Partition coefficient: n-octanol/water : No Data Available.  
Viscosity, dynamic : Not applicable.  
Relative vapor density : Not applicable.

# SAFETY DATA SHEET

**LLD Widespec**

Gen. Variant: SDS\_US\_GHS

Version 1.0

Revision Date 04/21/2018

Print Date 08/23/2018

SDS No.: LLDBWS

Evaporation rate : Not applicable.

Explosive properties : No Data Available.

Remarks - Other information : No additional information available.

## SECTION 10. STABILITY AND REACTIVITY

Reactivity : No known reactivity hazards.

Chemical stability : Stable under normal conditions.

Conditions to avoid : Avoid contact with strong oxidizers, excessive heat, sparks or open flame.

Materials to avoid : Material may be softened by some hydrocarbons.

Hazardous decomposition products : Not expected to decompose under normal conditions.

Thermal decomposition : Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.

Hazardous reactions : Will not occur.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Acute toxicity

**Acute oral toxicity** : Not classified

**Acute inhalation toxicity** : Not classified

**Acute dermal toxicity** : Not classified

**Skin corrosion/irritation** : Not a skin irritant.

**Serious eye damage/eye irritation** : Not an eye irritant.  
Mechanical irritation is possible.

**Respiratory or skin sensitization** : Not classified



# SAFETY DATA SHEET

**LLD Widespec**

Gen. Variant: SDS\_US\_GHS

Version 1.0

Revision Date 04/21/2018

Print Date 08/23/2018

SDS No.: LLDBWS

## Chronic toxicity

Carcinogenicity :  
Not classified  
Not listed by IARC, NTP, OSHA or EPA.

Germ cell mutagenicity : Not classified

## Reproductive toxicity

Effects on fertility /  
Effects on or via lactation : Not classified

Effects on Development : Not classified

**Target Organ Systemic  
Toxicant - Single exposure** : The substance or mixture is not classified as specific target  
organ toxicant, single exposure.

**Target Organ Systemic  
Toxicant - Repeated  
exposure** : The substance or mixture is not classified as specific target  
organ toxicant, repeated exposure.

**Aspiration hazard** : Not applicable.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicology Assessment

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Not classified

### Persistence and degradability

**Biodegradability** : Not expected to be biodegradable.

### Bioaccumulative potential

**Bioaccumulation** : This material is not expected to bioaccumulate.

### Mobility in soil

**Additional advice** : This material is not volatile and insoluble in water.

# SAFETY DATA SHEET

**LLD Widespec**

Gen. Variant: SDS\_US\_GHS

Version 1.0

Revision Date 04/21/2018

Print Date 08/23/2018

SDS No.: LLBWS

## Environmental fate and pathways

### Results of PBT and vPvB assessment

Not applicable.

### Other adverse effects

**Additional ecological information** : Ecotoxicity is expected to be minimal based on the low water solubility of polymers.

## SECTION 13. DISPOSAL CONSIDERATIONS

Further information : All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.

## SECTION 14. TRANSPORT INFORMATION

Not regulated for transport

## SECTION 15. REGULATORY INFORMATION

If identified components of this product are listed under the TSCA 12(b) Export Notification rule, they will be listed below.

### SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

### SARA 313

This product contains no known chemicals regulated under SARA 313.

### State Reporting

This material is not known to contain a chemical substance known to the State of California to cause cancer, reproductive, or developmental toxicity under California Proposition 65. However, Trademark Plastics has not tested for the presence of listed chemical substances.

This product contains no known chemicals regulated by New Jersey's Worker and Community Right to Know Act.

No components are subject to the Massachusetts Right to Know Act.

This product contains no known chemicals regulated by Pennsylvania's Right to Know Act.

### Other international regulations

SAFETY DATA SHEET

**LLD Widespec**

Gen. Variant: SDS\_US\_GHS

Version 1.0

Revision Date 04/21/2018

Print Date 08/23/2018

SDS No.: LLD2017

**Global Inventory Status**

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

\*Additional Explanatory Status Statements follow the table, as necessary.


Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Not Determined

**SECTION 16. OTHER INFORMATION**

**Further information**


**HMIS Classification**

: Health Hazard: 1  
 Flammability: 1  
 Physical hazards: 0



**NFPA Classification**

: Health Hazard: 1  
 Fire Hazard: 1  
 Instability: 0



**Other Information**

HMIS rating scale (0 = minimal hazard; 4 = severe hazard)  
 NFPA rating scale (0 = minimal hazard; 4 = severe hazard)

**Material safety datasheet sections which have been updated:**



# SAFETY DATA SHEET

**LLD Widespec**

Gen. Variant: SDS\_US\_GHS

Version 1.0

Revision Date 04/21/2018

Print Date 08/23/2018

SDS No.: LLBWS

**Material safety datasheet sections which have been updated:**

Updated format ; First Edition April 15 2018

---

**Disclaimer**

This document is generated for the purpose of distributing health, safety, and environmental data.

Information is correct to the best of our knowledge at the date of the SDS publication.

It is not a specification sheet nor should any displayed data be construed as a specification.

Before using a product sold by a company of the Trademark Plastics family of companies, users should make their own independent determination that the product is suitable for the intended use and can be used safely and legally. SELLER MAKES NO WARRANTY; EXPRESS OR IMPLIED (INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY WARRANTY) OTHER THAN AS SEPARATELY AGREED TO BY THE PARTIES IN A CONTRACT.

This product(s) may not be used in:

(i) any U.S. FDA Class I, Health Canada Class I, and/or European Union Class I medical devices, without prior notification to Seller for each specific product and application; or (ii) the manufacture of any of the following, without prior written approval by Seller for each specific product and application: U.S. FDA Class II Medical Devices; Health Canada Class II or Class III Medical Devices; European Union Class II Medical Devices; film, overwrap and/or product packaging that is considered a part or component of one of the aforementioned medical devices; packaging in direct contact with a pharmaceutical active ingredient and/or dosage form that is intended for inhalation, injection, intravenous, nasal, ophthalmic (eye), digestive, or topical (skin) administration; tobacco related products and applications, electronic cigarettes and similar devices, and pressure pipe or fittings that are considered a part or component of a nuclear reactor. Additionally, the product(s) may not be used in: (i) U.S. FDA Class III Medical Devices; Health Canada Class IV Medical Devices; European Class III Medical Devices; (ii) applications involving permanent implantation into the body; (iii) life-sustaining medical applications; and (iv) lead, asbestos or MTBE related applications. All references to U.S. FDA, Health Canada, and European Union regulations include another country's equivalent regulatory classification.

